

Dexxo Compact 750 io



- ✓ Manufacturer: Somfy
- ✓ Convenient programming and diagnostics (Tahoma PRO and Serve-e-Go)
- ✓ Ready to operate in less than 90 seconds
- ✓ Integrated obstacle detection
- ✓ Compatibility with TaHoma® switch control unit
- ✓ Built-in LED lighting
- ✓ Standby power consumption <0.5 W
- ✓ maximum door size: 10 m²

The Dexxo Compact io garage door opener for sectional doors is an attractive choice for manufacturers, installers, and users due to its numerous conveniences. It supports doors with a surface area up to 10 m².

The Dexxo Compact io remote controls are pre-paired at the factory. Installation is quick thanks to Plug and Play technology and only requires pressing the "set" button. The opener automatically sets the end positions, and additional settings can be configured via the Tahoma PRO app or buttons on the device. The Dexxo Compact io also allows setting intermediate door positions, e.g., for ventilating the garage.

The opener is compatible with the Serv-e-Go app, allowing for connection for diagnostics and servicing.

The Tahoma PRO and Serv-e-Go apps require the TaHoma® switch control unit, which integrates io devices into one system. It allows monitoring and controlling the door with a smartphone from anywhere with internet access. The control unit is compatible with voice assistants and enables creating usage scenarios and control based on geolocation.

Safety is ensured by an amperometric sensor that stops the door movement in case of an obstacle, and optionally, photoelectric cells can be added to monitor the passage light.

In standby mode, the Dexxo Compact io consumes minimal energy. It also features independently controlled LED lighting and the option to add an emergency battery or other safety accessories.