

# MB-79N



- ✓ installation depth: 70 mm
- ✓ available in three thermal versions: E, ST, and SI
- ✓ glazing with units up to 63 mm wide (windows) or up to 54 mm wide (fixed units/doors)
- ✓ windows available in RC2 and RC3 anti-burglary classes
- ✓ coated in the full RAL K7 palette and customized according to particular powder code

**0.9**

U<sub>w</sub> for U<sub>g</sub> = 0.5  
(Ultimate spacer)\*

**2**

Gaskets

**3**

Chambers

The MB-79N aluminium window and door system is one of the most popular solutions made of this material for energy-efficient construction. Its modern design, combined with good performance and availability in large dimensions, makes it an excellent choice not only for residential buildings.

## Key features of the MB-79N system:

- modern design perfectly suited to modern, elegant architecture
- three thermal options, including a solution for highly energy-efficient buildings
- effective sound insulation thanks to the possibility of using glazing up to 63 mm thick

## Choose the MB-79N if you:

- appreciate the minimalist aesthetics of aluminium windows with distinctive right angles
- enjoy large glazed areas and interiors filled with natural light

- seek joinery in vivid colours and want to match its shade precisely

## **Learn more about MB-79N:**

- frame depth: 70 mm
- sash depth: 79 mm (windows), 70 mm (doors)
- maximum dimensions of the sash of tilt and turn window – H up to 2700 mm, L up to 1700 mm
- maximum dimensions of the door wing – H up to 2800 mm, L up to 1400 mm

\*The above value of  $U_w$  is given for a reference window with dimensions of 1230 x 1480 mm, in the best thermal variant.